



L-BOXX Data Sheet



L-BOXX

1. Measures

| Description | Outer Measures (W x D x H) | Inner measures (W x D x H)* |
|-------------|----------------------------|--|
| L-BOXX 102 | 442 x 357 x 117 mm | 378 x 313 x 63.5 mm |
| L-BOXX 136 | 442 x 357 x 151 mm | 378 x 311 x 99.5 mm |
| L-BOXX 238 | 442 x 357 x 253 mm | 378 x 304 x 200.5 mm |
| L-BOXX 374 | 442 x 357 x 389 mm | 378 x 294 x 337.5 mm |
| LS-BOXX 306 | 442 x 357 x 322 mm | 378 x 311 x 99.5 mm + additional space below |

*The contour of our L-BOXX is not ashlar-formed. The inner measures are the minimum measures. The actual measurement of some BOXXes may be significantly higher.

2. Empty Weight

| | |
|-------------|--------|
| L-BOXX 102 | 2.1 kg |
| L-BOXX 136 | 2.2 kg |
| L-BOXX 238 | 2.8 kg |
| L-BOXX 374 | 3.4 kg |
| LS-BOXX 306 | 2.7 kg |

3. Material

| | |
|------------------------------|-----------------------------------|
| Floor | ABS (Acrylnitril-Butadien-Styrol) |
| Cover | ABS (Acrylnitril-Butadien-Styrol) |
| Handle | ABS (Acrylnitril-Butadien-Styrol) |
| Safety catch | PA6 (Polyamid 6) |
| Front handle | ABS (Acrylnitril-Butadien-Styrol) |
| Connecting clamp | PA6 (Polyamid 6) |
| Molded recess | ABS (Acrylnitril-Butadien-Styrol) |
| Molded recess 102 | ABS (Acrylnitril-Butadien-Styrol) |
| Foldable handle bar | ABS (Acrylnitril-Butadien-Styrol) |
| Intermediate floor (LS-BOXX) | ABS (Acrylnitril-Butadien-Styrol) |
| Side part (LS-BOXX) | ABS (Acrylnitril-Butadien-Styrol) |

4. Mechanical load capacity

| | |
|-------------------------|-------|
| Max. load single box | 12 kg |
| Max. load handle* | 40 kg |
| Allowable load on cover | 85 kg |

*If the L-BOXX tower is carried on the handle.



L-BOXX Data Sheet



5. Temperature Range

The L-BOXX can be used from -30°C to +80°C.

6. Watertightness

The L-BOXX is splash water and rainwater proof. Water can enter at stagnant moisture.

i-BOXX

1. Measures

| Description | Outer Measures (W x D x H) | Inner measures (W x D x H)* |
|-------------|----------------------------|-----------------------------|
| i-BOXX 53 | 367 x 316 x 53 mm | 340 x 261 x 44 mm |
| i-BOXX 72 | 367 x 316 x 72 mm | 340 x 261 x 63 mm |
| LS-Tray 92 | 367 x 314 x 92 mm | 340 x 261 x 89 mm |

2. Empty Weight

| | |
|------------|--------|
| i-BOXX 53 | 0.8 kg |
| i-BOXX 72 | 0.9 kg |
| LS-Tray 92 | 0.6 kg |

3. Material

| | |
|-----------------|-----------------------------------|
| Floor | ABS (Acrylnitril-Butadien-Styrol) |
| Cover | PC (Poly-Carbonat) |
| Stackable hinge | PP (Poly-Propylen) |

7. Mechanical load capacity

| | |
|-------------------|------|
| Max. load i-BOXX | 3 kg |
| Max. load LS-Tray | 3 kg |